Model





| Resolution | 640×480/12μm | |
|-------------------------------------|---|-----------------|
| NETD | ≤40mK | |
| Focal Length of Objective Lens | f35/F0.9 | f50/F1.0 |
| FOV | 12.5°x9.4° | 8.8°x6.6° |
| Recognization Range(Deer) | 830m | 1180m |
| Recognization Range(Vehicle) | 1490m | 2130m |
| Digital Zoom | 1x/2x/4x/8x | |
| Recommended Day Scope Magnification | 1x-9x | |
| Image Polarity | White-hot,black-hot,red-hot,iron-red,rainbow,and outline | |
| Eye Relief | 25mm~60mm | |
| Diopter | -4D~+2D | |
| Screen | 1.03",2560x1920AMOLED | |
| Battery | 3.7V/4400mAh | |
| Max.Operating Time(at t=22°C) | ≥6h | |
| External Power Supply | 5V (USBC) | |
| Memory Capacity | 64GB | |
| Impact | 1200g /0.3ms | |
| Ingress Protection Rating | IP67 | |
| Operating Temperature | -20°C~+50°C | |
| Weight | <920g | <940g |
| Dimensions | 267mm×77mm×76mm | 280mm×77mm×76mm |
| APP | Support | |
| Optional Extended Functions | Bluetooth remote controller Laser rangefinder 1000, with a maximum measuring range of 1,000r (500m for deer) Laser rangefinder 2000, with a maximum measuring range of 2,000r (1,000m for deer) | |



IRay Technology Co., Ltd.

Tel: 400-998-3088 Fax: +86-535-3410604
Mail: infirayoutdoor@infiray.com Web: www.infirayoutdoor.com
Add: 11th Guiyang Street, YEDA, Yantai 264006, P.R.China



equipped with optional external LRF and ballistic calculation to make accuracy up to ±1MOA. It adopts a 2K level 2560×1920 full-color OLED display, which provides excellent display performance while its eyepieces are designed with user comfort and safety in mind. Hybrid aims to bring you a hunt like never before.









More Functional



Support both Riflescope and Clip-on Mode

The two modes can be switched in seconds without changing the eyepiece.





- Recoil-Activated Video

Hybrid adds a recoil-activated video function to lock the 30-second clips before and after shooting so that no wonderful moments are missed.

Support video & audio recording. Images and videos can be played back within devices and transmitted through WiFi.



Recoil **Activated Video**



WIFI



Audio Recording

Ultra Clear



2K Level Display

Apply a 2K level display to the outdoor hunting field, high resolution 2560×1920 silicon-based OLED display, high contrast and low power consumption. Able to bring users an ultra-clear and comfortable visual experience.





More Comfortable





Extra Large Eyebox

The larger eyebox makes it easy to see clear images in dynamic situations. The 60 mm long eye relief design avoids eye injury caused by the recoil of shooting.

Ultra Precise



- More Accurate up to ±1MOA

Hybrid supports external laser range finder to generate accurate aiming points through automatic ballistic calculation of rangefinding results. The accuracy of Hybrid can reach ±1MOA.



Ballistic Calculation

The function ballistic calculation is especially designed for the device to make its more accuracy, which could bring users a remarkable hunting experience.

More Reliable



- Waterproof & Dustproof

The whole machine is waterproof (IP67) and dustproof, which can be used in harsh conditions.



Recoil-absorbing Mount

Hybrid passes the rigorous reliability test. The test result shows it does not move from the zero position after more than 20,000 times of 1200g impact. Hybrid is suitable for the long-term use of a gun that is chambered for the 7.62×39mm cartridge.

