| Model  | AP13  | AL19        | AL25       |
|--|---|-------------|------------|
| Detector Specifications                                  |   |             |            |
| Туре   | Uncooled Vox                                |             |            |
| Resolution   | 256×192                                     | 384×288     |            |
| Pixel Size, µm   | 12  |             |            |
| NETD, mK   | ≤ 40  |             |            |
| Frame Rate, Hz   | 25  | 50          |            |
| Optical Specifications                                   |   |             |            |
| Objective Lens, mm                                       | 13  | 19          | 25         |
| FOV  | 13.5°×10.1°                                 | 13.8°×10.4° | 10.5°×7.9° |
| Digital Zoom, x  | 1/2   | 1/2/4       |            |
| Diopter, D   | -3 ~ +1                                     | -7 ~ +2     |            |
| Detection Range, m<br>(Target Size: 1.7m×0.5m, P(n)=99%) | 675   | 986         | 1298       |
| Display Specifications                                   |   |             |            |
| Туре   | LCOS OLED                                   |             |            |
| Resolution   | 720×540                                     | 640×400     |            |
| Battery Power Supply                                     |   |             |            |
| Battery Type / Capacity / Output Voltage                 | Built-in lithium ion battery / 3.6Ah / 3.6V |             |            |
| Working Hours (22°C), h*                                 | 9.5   | 7.5         |            |
| External Power Supply                                    | 5V (Type C)                                 |             |            |
| Physical Specifications                                  |   |             |            |
| Ingress Protection Rating                                | IP67  |             |            |
| Memory Capacity, GB                                      | 32  |             |            |
| Wi-Fi / APP  | Support (InfiRay outdoor)                   |             |            |
| Operating Temperature, °C                                | -10 ~ +50                                   | -20 ~ +50   |            |
| Weight, g  | <340  | <340 <350   |            |
| Dimensions, mm   | 160×60×60 169×60×60                         |             |            |



## IRay Technology Co., Ltd.

Tel: 400-998-3088Fax: +86-535-3410604Mail: infirayoutdoor@infiray.comWeb: www.infirayoutdoor.comAdd: 11th Guiyang Street, YEDA, Yantai 264006, P.R.China





Thermal Imaging Monocular

**AFFO** Series

The AFFO Series handheld thermal imager is an entry-level thermal imager for hunting users, featuring both a fashionable appearance and a more compact size. The AFFO Series uses a self-developed 12µm detector with 256×192/384×288 resolution to produce crisp images and supports photo taking and video recording with its built-in high-speed 32GB storage capacity.

















# - High-performance Detector 12µm

The AFFO Series adopts 12 µm 256×192/384×288 resolution uncooled Vox thermal imaging sensor, the self-developed high-performance sensor enables crisp HD images.

AFFO AP13



HDMI

multimedia interface) uses full digital signal transmission, which not only provides full digital video signal, but also transmits audio at the same time. This device can be directly connected to HD screens, laptops, etc. for high-quality display.



Low power elements used in AFFO Series provide sufficient operation time. Up to 9.5 hours operational battery life.






The AFFO Series features additional practical functions including stadiametric rangefinding and PIP. Its adapter is equipped with multiple travel charging headers to meet the needs of use in different countries and regions.

#### 1.Stadiametric Rangefinding:

Facilitate confirmation of prey distance and provide position reference for hunting



Stadiametric Rangefinding

### More image modes to cope with different scenarios

Hot target highlight mode provides better object highlighting capability with more options of white hot, black hot, red-hot and color palette. Wider detection and operating temperature ranges with hotspot tracking function.



The 32GB memory of AFFO Series makes it possible to record all night, meeting the requirements of whole-hunting process recording.





#### 2.PIP:

The screen of cursor position is magnified twice to highlight the target and assist in observing the target details



PIP

## -O- Upgraded Protection

#### 1. Upgraded lens protection:

Durable rigid plastic lens cap with higher hardness and impact resistance;

#### 2. Upgraded waterproofing:

External screen is used in rainy days for outdoor scenarios to prevent water flowing into the interface.